

WET DIAMOND BLADES- Asphalt and Green Concrete

ASPHALT AND GREEN CONCRETE BLADES							
SIZE	STANDARD GOLD (S) with Wear Retardant (.250 diamond depth)	HEAVY DUTY ORANGE (H) with Wear Retardant (.250 diamond depth)			PREMIUM BLACK (P) with Wear Retardant (.275 diamond depth)		
	SLANT SEGMENT (X)	SLANT SEGMENT (X)	DIAMOND INSERTED (Q)	RADIUS ANGLE SEGMENT (R)	SLANT SEGMENT (X)	DIAMOND INSERTED (Q)	RADIUS ANGLE SEGMENT (R)
12" X .125	\$415	\$464	\$510	\$479	\$557	\$699	\$588
12" X .140	476	531	583	-	652	789	672
12" X .187	571	639	700	-	756	945	816
12" X .250	689	777	853	-	952	1,162	1,008
12" X .375	983	1,114	1,220	-	1,369	1,659	
14" X .125	501	569	610	591	685	824	727
14" X .140	603	658	702	681	792	938	835
14" X .187	710	778	833	809	943	1,112	1,000
14" X .250	867	956	1,026	997	1,170	1,381	1,248
14" X .375	1,235	1,366	1,464	-	1,685	1,978	1,801
16" X .125	592	660	730	681	813	993	834
16" X .140	675	752	827	-	924	1,114	948
18" X .125	668	745	820	771	876	1,096	925
18" X .140	769	857	938	885	1,007	1,239	1,059
18" X .155	849	947	1,033	978	1,119	1,359	1,169
18" X .175	-	-	-	-	1,139	1,473	1,230
18" X .187	902	1,010	1,111	1,040	1,194	1,463	1,264
18" X .250	1,099	1,237	1,364	1,263	1,481	1,810	1,576
20" X .125	756	821	910	829	967	1,211	1,015
20" X .140	859	933	1,027	960	1,104	1,355	1,149
20" X .155	-	1,023	1,122	-			
24" X .155	1,117	1,214	1,322	1,252	1,438	1,746	1,496
24" X .175	-	1,309	1,487	1,408	1,580	1,892	1,625
24" X .187	1,248	1,362	1,570	1,492	1,639	1,977	1,698
26" X .155	1,233	1,337	1,455	-	1,604	1,918	1,649
26" X .175	-	-	1,570	1,492	1,741	2,079	1,791
26" X .187	1,415	1,529	1,664	1,583	1,849	2,200	1,904
30" X .175	1,432	1,562	1,698	1,620	1,891	2,255	1,950
30" X .187	1,481	1,620	1,763	1,681	1,971	2,349	2,033
32" X .187	-	1,780	1,929	-	2,132	2,559	2,284
36" X .175	-	-	2,160	-	2,397	2,822	
36" X .187	1,858	2,072	2,237	-	2,490	2,934	2,573

ASPHALT, GREEN CONCRETE & ASPHALT over CONCRETE BLADE SPECS *						
Aggregate Type	Asphalt Low HP Spec.#	Asphalt High HP Spec.#	Green Concrete Low HP Spec.#	Green Concrete High HP Spec.#	Asphalt Over Concrete Low HP Spec.#	Asphalt Over Concrete High HP Spec.#
Hard	A350	A608	G66DW	G68DW	AC62DW	AC62DW
Med. Hard	A605	A627	G606	G606	AC62DW	AC62DW
Medium	A606	A627	G615	G610	AC64DW	AC64DW
Med. Soft	A615	A635	G660	G660	AC64DW	AC64DW
Soft	A635	A665	G670	G670	AC64DW	AC66DW

Select Grade: S Standard (Gold) H Heavy Duty (Orange) P Premium (Black)

* These are recommendations for starting specifications. Low HP = 18HP or lower. High HP = 20 HP or higher.

Most asphalt, green concrete and asphalt over concrete blades are laser welded.

Any of these blades can be laser welded or silver brazed upon request.